

### **IN THE CLAIMS:**

Claims 1, 4-6, 9, 11-13, 16, 17 and 20 are amended herein. Claims 21-26 are added. All pending claims are produced below. In addition, the status of each is also indicated below.

1. (Currently Amended) An electronic device, comprising:

a radio unit configured to communicate with a network;

at least one memory device configured to store application and system programs; and

a processing unit coupled to said radio unit and said at least one memory device, said processing unit configured to run the application and system programs;

wherein at least one of the application and system programs ~~include~~ comprises a notification program configured to display a software enabled switch ~~displayed on the device screen~~ for enabling ~~and disabling~~ the radio unit ~~from a disabled state in response to a program attempting to utilize the radio unit~~ while leaving the processing unit in an operation state, ~~the device screen being configured to display and further configured to display~~ information for a context associated with a state of the software enabled switch.

2. (Previously Presented) An electronic device comprising:

a radio unit configured to communicate with a network;

at least one memory device configured to store application and system programs; and

a processing unit couples to said radio unit and said at least one memory device, said processing unit configured to run the application and system programs;

wherein:

at least one of the application and system programs includes a software enabled switch for enabling and disabling the radio unit;

at least one of said application and system programs is a program that utilizes the radio unit; and

at least one of said application and system programs comprises a notification program configured to notify a user that the radio unit is disabled when invoking a program that is configured to utilize the radio unit and to display a software enabled switch, the software enabled switch further configured to either enable the radio unit for use by the program configured to utilize the radio unit or maintain the radio unit as disabled.

3. (Cancelled)

4. (Currently Amended) The electronic device according to Claim 1, further comprising wherein:

~~said device further comprises a display screen; and , wherein~~

at least one of ~~said system and application~~ the application and system programs ~~are is~~ configured to generate a graphical user interface on the display screen, the

graphical user interface having at least one soft button programmed to enable ~~and or~~ disable ~~said the~~ radio ~~device~~ unit.

5. (Currently Amended) The electronic device according to Claim 4, wherein ~~said the~~ graphical user interface ~~is a GUI having~~ has a first soft button labeled “*RADIO ON*,” and a second soft button labeled “*RADIO OFF*,” ~~and an enablement~~ a status of the radio ~~device is unit being~~ indicated by the corresponding soft button highlighted in one of bold, inverse video, flashing, or other indicators.

6. (Currently Amended) The electronic device according to Claim 1, further comprising a hard button programmed to enable and disable the radio ~~device~~ unit, wherein ~~said the~~ hard button is a toggle switch that is activated by engaging the ~~hard button toggle switch~~ for a predetermined length of time.

7. (Original) The electronic device according to Claim 6, wherein said hard button has at least one additional program invoked by pressing the hard button for a time period less than said predetermined length of time.

8. (Original) The electronic device according to Claim 6, wherein said predetermined length of time is approximately 1 second.

9. (Currently Amended) The electronic device according to Claim 1, wherein said software enabled switch comprises:

a user interface with a drop down menu having user selectable options for Radio On, Radio Off, and Schedule, and

a program configured to implement an option selected by ~~the~~ a user.

10. (Original) The electronic device according to Claim 1, wherein the application and system programs include a scheduling application that provides user modifiable start and stop times that indicate when the radio unit is enabled and disabled.

11. (Currently Amended) A notification mechanism for notifying a user of a status of an RF device in an RF capable device, wherein the RF capable device includes a processing unit for running applications and a user interface, ~~said~~ the notification mechanism comprising:

a check mechanism configured to check an enablement status of the RF device;

a user interface mechanism configured to display a status of the RF device, ~~and~~ a software enabled switch on a touch-sensitive screen, and information for a context associated with a program that is previously invoked that requires RF capabilities, providing the user with an option to continue with the program ~~requiring RF capabilities~~ and automatically enable the RF device or discontinue the program ~~requiring RF capabilities~~ without enabling the RF device; and

an RF alarm mechanism configured to identify the program ~~a program that is previously invoked that requires the RF capabilities of the RF capable device~~, wherein upon identifying the program, the RF alarm mechanism ~~wakes the notification mechanism from a "sleep" mode and the notification mechanism checks~~ invokes the check mechanism to check the enablement status of the RF device using said check mechanism, and if the RF device is not enabled, ~~the notifications mechanism~~ invokes the user interface mechanism.

12. (Currently Amended) A method of notifying a user of an RF enablement status of a device having RF capabilities, comprising the steps of:

identifying ~~the~~ an invocation of a mechanism requiring access to the RF capabilities;

determining the RF enablement status of the ~~RF~~ device;

if the RF enablement status of the device is ~~not enabled~~ in a disabled state:

~~prompting a notifying the~~ user ~~of the device~~ if the mechanism is to be granted

RF access to the RF capabilities by displaying a software enabled switch and displaying information for a context associated with a state of the software enabled switch, and

~~retrieving~~ receiving a user input regarding whether ~~RF access to the RF capabilities~~ should be granted to the mechanism requiring RF-  
access;

if the user input indicates the mechanism is to be granted ~~RF access to the RF capabilities~~:

automatically enabling the RF ~~device capabilities~~, and

allowing the mechanism ~~requiring RF access to continue and~~ access  
the RF ~~device capabilities~~; and

if the user input indicates the mechanism ~~should is not to~~ be granted ~~RF access to the RF capabilities, then~~;

shutting down the mechanism ~~requiring RF access~~ without enabling  
the RF ~~device capabilities~~.

13. (Currently Amended) The electronic device of Claim 1, wherein  
at least one of the application and system programs ~~include~~ includes a prompting  
mechanism configured to display a prompt to a user to determine if the  
radio unit is to be enabled before enabling the radio unit.
14. (Previously Presented) The electronic device according to Claim 13,  
wherein:  
  
said application and system programs comprise a notification mechanism to identify  
when the radio unit is enabled.
15. (Previously Presented) The electronic device according to Claim 14, wherein  
the notification mechanism comprises display of an airplane icon.
16. (Currently Amended) The electronic device according to Claim 13, further  
comprising a shutdown device configured to maintain the radio unit in a ~~non-enabled~~ the  
disabled state, maintain the processing unit in an operational state, and shut down an  
application program that utilizes the radio unit upon a negative response to the prompt from  
the user.
17. (Currently Amended) The electronic device according to Claim 1, wherein  
the information for a context associated with a state of the software enabled switch further  
~~comprising~~ comprises a status display indicating enablement of the radio unit, ~~and wherein~~  
the status display ~~comprises~~ comprising an airplane icon.
18. (Previously Presented) The electronic device according to Claim 2, further  
comprising a status display indicating enablement of the radio unit, wherein the status display  
comprises an airplane icon.

19. (Previously Presented) The notification mechanism according to Claim 11, further comprising a display indicating enablement status of the radio unit, wherein the display comprises an airplane icon.

20. (Currently Amended) The method according to Claim 12, further comprising the step of displaying the enablement status of the ~~RF~~ device using an icon that comprises an airplane.

21. (New) The electronic device according to Claim 2, further comprising:

a display screen, wherein at least one of the application and system programs is configured to generate a graphical user interface, the graphical user interface having a first soft button labeled “*RADIO ON*,” and a second soft button labeled “*RADIO OFF*,” a status of the radio unit being indicated by the corresponding soft button highlighted in one of bold, inverse video, flashing, or other indicators.

22. (New) The electronic device according to Claim 2, further comprising a hard button programmed to enable and disable the radio unit, wherein the hard button is a toggle switch that is activated by engaging the toggle switch for a predetermined length of time.

23. (New) The electronic device according to Claim 22, wherein the hard button has at least one additional program invoked by pressing the hard button for a time period less than the predetermined length of time.

24. (New) The electronic device according to Claim 22, wherein the predetermined length of time is approximately 1 second.

25. (New) The electronic device according to Claim 2, wherein the electronic device comprises a mobile phone.

26. (New) The electronic device according to Claim 25, wherein the mobile phone comprises a touch sensitive screen, the software enabled switch being displayed on the touch sensitive screen and being selectable.